



Feature

- Single Output to 36W
- Fixed AC Pin
- IEC/EN/UL 60950-1 2nd
- DoE Level VI & CoC Tier 2 Efficiency
- Low Ripple Noise

FPA036 Series

| Model | FPA036-05* | FPA036-06* | FPA036-09* | FPA036-12* | FPA036-15* | FPA036-18* | FPA036-20* | FPA036-24* | FPA036-28* | FPA036-48* | FPA036-56* |
|-----------------|--------------------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Output Voltage | 5V | 6V | 9V | 12V | 15V | 18V | 20 | 24V | 28 | 48V | 56V |
| Output Current | 5A | 5A | 4A | 3A | 2.4A | 2A | 1.8A | 1.5A | 1.28A | 0.75A | 0.64A |
| Max Power | 25W | 30W | 36W | 36W | 36W | 36W | 36W | 36W | 36W | 36W | 36W |
| Input Power | 90 - 264 Vac | | | | | | | | | | |
| Input Frequency | 47 - 63 Hz | | | | | | | | | | |
| Input Current | 0.8A Max. | | | | | | | | | | |
| Regulation | Line 1%, Load 5% | | | | | | | | | | |
| Ripple & Noise | 1~2% Vp-p Max. | | | | | | | | | | |
| Efficiency | DoE Level VI & CoC Tier 2 | | | | | | | | | | |
| Operating Temp. | 0 to 40C | | | | | | | | | | |
| Storage Temp. | -20 to +85C | | | | | | | | | | |
| OVP | Auto Recovery | | | | | | | | | | |
| SCP | Auto Recovery | | | | | | | | | | |
| Standard | IEC/EN/UL 60950-1 2nd Edition, | | | | | | | | | | |
| Safety | CB/ cULus/FCC/GS/CE/PSE/RCM | | | | | | | | | | |