

Feature

- Single Output to 36W
- Interchangeable AC Pin
- IEC/EN/UL 60950-1 2nd
- DoE Level VI & CoC Tier 2 Efficiency
- Low Ripple Noise



FPA036 Series

Model	FPA036-05X	FPA036-06X	FPA036-09X	FPA036-12X	FPA036-15X	FPA036-18X	FPA036-20X	FPA036-24X	FPA036-28X	FPA036-48X	FPA036-56X
Output Voltage	5V	6V	9V	12V	15V	18V	20	24V	28	48V	56V
Output Current	5A	5A	4A	3A	2.4A	2A	1.8A	1.5A	1.28A	0.75A	0.64A
Max Power	25W	30W	36W	36W	36W	36W	36W	36W	36W	36W	36W
Input Power	90 - 264 Vac										
Input Frequency	47 - 63 Hz										
Input Current	0.8A Max.										
Regulation	Line 1%, Load 5%										
Ripple & Noise	1~2% Vp-p Max.										
Efficiency	DoE Level VI & CoC Tier 2										
Operating Temp.	0 to 40C										
Storage Temp.	-20 to +85C										
OVP	Auto Recovery										
SCP	Auto Recovery										
Standard	IEC/EN/UL 60950-1 2nd Edition,										
Safety	CB/ cULus/FCC/GS/CE/PSE/RCM										

