



## Feature

- Single Output to 65W
- Interchangeable AC Pin
- IEC/EN/UL 60950-1 2nd
- DoE Level VI & CoC Tier 2 Efficiency
- Low Ripple Noise

## FPA065 Series

Model	FPA065-05X	FPA065-09X	FPA065-12X	FPA065-15X	FPA065-19X	FPA065-24X	FPA065-36X	FPA065-48X	FPA065-56X
Output Voltage	5V	9V	12V	15V	19V	24V	36V	48V	56V
Output Current	8A	6A	5A	4.34A	3.4A	2.7A	1.8A	1.35A	1.16A
Max Power	40W	54W	60W	65W	65W	65W	65W	65W	65W
Input Power	90 - 264 Vac								
Input Frequency	47 - 63 Hz								
Input Current	1.5A Max.								
Regulation	Line 1%, Load 5%								
Ripple & Noise	1~2% Vp-p Max.								
Efficiency	DoE Level VI and CoC Tier 2								
Operating Temp.	0 to 40C								
Storage Temp.	-20 to +85C								
OVP	Auto Recovery								
SCP	Auto Recovery								
Standard	IEC/EN/UL 60950-1 2nd Edition								
Safety	CB/ cULus/FCC/GS/CE/PSE/BSMI/RCM								

