

Feature

- Single Output to 48W Max.
- Class I Power Supply
- Interchangeable AC Pin
- IEC/EN/UL 60950-1 2nd
- DoE Level VI & CoC Tier 2 Efficiency
- Low Ripple Noise



FPB048 Series

Model	FPB048 -12X	FPB048 -15X	FPB048 -18X	FPB048 -19X	FPB048 -24X	FPB048 -28X	FPB048 -36X	FPB048 -48X
Output Voltage	12	15V	18V	19V	24V	28V	36V	48V
Output Current	4A	3.2A	2.66A	2.56A	2A	1.71A	1.33A	1A
Max Power	48W	48W	48W	48W	48W	48W	48W	48W
Input Power	90 - 264 Vac							
Input Frequency	47 - 63 Hz							
Input Current	1.0 ~ 1.5A Max.							
Regulation	Line 1%, Load 5%							
Ripple & Noise	1~2% Vp-p Max.							
Efficiency	DoE Level VI & CoC Tier 2							
Operating Temp.	0 to 40C							
Storage Temp.	-20 to +85C							
OVP	Auto Recovery							
SCP	Auto Recovery							
Standard	IEC/EN/UL 60950-1 2nd Edition,							
Safety	CB/ cULus/FCC/GS/CE/PSE/RCM							