



Feature

- Single Output to 36W
- Desktop Type Class I & II Power Supply
- IEC/EN/UL 60950-1 2nd
- DoE Level VI & CoC Tier 2 Efficiency

FPA036 Series

Model	FPA036 -V*05	FPA036 -V*06	FPA036 -V*09	FPA036 -V*12	FPA036 -V*15	FPA036 -V*18	FPA036 -V*20	FPA036 -V*24	FPA036 -V*28	FPA036 -V*48	FPA036 -V*56
Output Voltage	5V	6V	9V	12V	15V	18V	20	24V	28	48V	56V
Output Current	5A	5A	4A	3A	2.4A	2A	1.8A	1.5A	1.28A	0.75A	0.64A
Max Power	25W	30W	36W	36W	36W	36W	36W	36W	36W	36W	36W
Input Power	90 - 264 Vac										
Input Frequency	47 - 63 Hz										
Input Current	0.8A Max.										
Regulation	Line 1%, Load 5%										
Ripple & Noise	1~2% Vp-p Max.										
Efficiency	DoE Level VI & CoC Tier 2										
Operating Temp.	0 to 40C										
Storage Temp.	-20 to +85C										
OVP	Auto Recovery										
SCP	Auto Recovery										
Standard	IEC/EN/UL 60950-1 2nd Edition,										
Safety	CB/ cULus/FCC/GS/CE/PSE/RCM										
AC Inlet	Class I C14 & C6 ; Class II C6 available										