



Feature

- Single Output to 120W
- Desktop Class I & II Power Supply
- 60950-1 2nd Edition
- DoE Level VI Efficiency & CoC Tier 2
- Low Ripple Noise

FWT120 Series

Model	FWT120 -V*12	FWT120 -V*121	FWT120 -V*135	FWT120 -V*15	FWT120 -V*16	FWT120 -V*18	FWT120 -V*19	FWT120 -V*20	FWT120 -V*24	FWT120 -V*48
Output Voltage	12V	12V	13.5V	15V	16V	18V	19V	20V	24V	48V
Output Current	9.5A	10A	8.44A	8A	7.5A	6.67A	6.32A	6A	5A	2.5A
Max Power	114W	120W	114W	120W	120W	120W	120W	120W	120W	120W
Input Power	90 - 264 Vac									
Input Frequency	47 - 63 Hz									
Input Current	1.6A Max.									
Regulation	Line 1%, Load 5%									
Ripple & Noise	1-2% Vp-p Max. at Full Load									
Efficiency	DoE Level VI and CoC Tier 2									
Operating Temp.	0 to 40C									
Storage Temp.	-20 to 80C									
OVP	Latch									
SCP	Auto Recovery									
Standard	IEC/EN/UL 60950-1 2nd Edition IEC/UL 62368									
Safety	CB/ cULus/FCC/CE									
AC Inlet	Class I C14 & C6 Available ; Class II C8 Available									

* could be A for C14 Inlet, B for C6 Inlet and C for C8 Inlet