

## Feature

- Single Output to 18W and 24W
- Fixed AC Pin
- IEC/EN/UL 60950-1 2nd
- USB Power Supply
- DoE Level VI & CoC Tier 2 Efficiency
- Low Ripple Noise



## FPU018 and FPU024 Series

Model	FPU018 -042*	FPU018 -05*	FPU018 -084*	FPU018 -09*	FPU018 -12*	FPU018 -15*	FPU018 -18*	FPU018 -36*	FPU018 -48*	FPU018 -56*	FPU024 -12*
Output Voltage	4.2V	5V	8.4V	9V	12V	15V	18V	36V	48V	56V	12V
Output Current	3A	3A	1.78A	1.66A	1.5A	1.2A	1A	0.5A	0.375A	0.32A	2A
Max Power	12.6W	15W	15W	15W	18W	18W	18W	18W	18W	18W	24W
Input Power	90 - 264 Vac										
Input Frequency	47 - 63 Hz										
Input Current	0.4A Max.										
Regulation	Line 1%, Load 5%										
Ripple & Noise	1~2% Vp-p Max.										
Efficiency	DoE Level VI & CoC Tier 2										
Operating Temp.	0 to 40C										
Storage Temp.	-20 to +85C										
OVP	Auto Recovery										
SCP	Auto Recovery										
Standard	IEC/EN/UL 60950-1 2nd Edition,										
Safety	CB/ cULus/FCC/GS/CE/PSE/RCM										