



## Feature

- Single Output to 15W
- Fixed AC Pin
- IEC/EN/UL 60950-1 2nd
- IEC/EN 60065
- UL 1310
- DoE Level VI Efficiency
- Low Ripple Noise

## FYA015 Series

Model	FYA015-													
	033*	042*	051*	052*	06*	084*	09*	012*	015*	018*	024*	028*	036*	040*
Output Voltage	3.3V	4.2V	5V	5V	6V	8.4V	9V	12V	15V	18V	24V	28V	36V	40V
Output Current	2A	2A	2A	3A	2A	1.6A	1.5A	1.25A	0.8A	0.75A	0.6A	0.53A	0.42A	0.38A
Max Power	6W	8.4W	10W	15W	12W	13.5W	13.5W	15W	12W	13.5W	14.4W	15W	15W	15W
Input Power	90 - 264 Vac													
Input Freq.	47 - 63 Hz													
Input Current	0.45A Max.													
Regulation	Line 1%, Load 5%													
Ripple & Noise	1~2% Vp-p Max.													
Efficiency	DoE Level VI													
Operating Temp.	0 to 40C													
Storage Temp.	-20 to +70C													
OVP	Auto Recovery													
SCP	Auto Recovery													
Standard	IEC/EN/UL 60950-1 2nd Edition, IEC/EN/UL 60065 UL 1310													
Safety	CB/ cULus/FCC/GS/CE/PSE													