

Feature

- Single Output to 15W
- Interchangeable AC Pin
- IEC/EN/UL 60950-1 2nd
- IEC/EN 60065
- UL 1310
- DoE Level VI Efficiency
- Low Ripple Noise



FYA015 Series

Model	FYA015-													
	033X	042X	051X	052X	06X	084X	09X	012X	015X	018X	024X	028X	036X	040X
Output Voltage	3.3V	4.2V	5V	5V	6V	8.4V	9V	12V	15V	18V	24V	28V	36V	40V
Output Current	2A	2A	2A	3A	2A	1.6A	1.5A	1.25A	0.8A	0.75A	0.6A	0.53A	0.42A	0.38A
Max Power	6W	8.4W	10W	15W	12W	13.5W	13.5W	15W	12W	13.5W	14.4W	15W	15W	15W
Input Power	90 - 264 Vac													
Input Freq.	47 - 63 Hz													
Input Current	0.45A Max.													
Regulation	Line 1%, Load 5%													
Ripple & Noise	1~2% Vp-p Max.													
Efficiency	DoE Level VI													
Operating Temp.	0 to 40C													
Storage Temp.	-20 to +70C													
OVP	Auto Recovery													
SCP	Auto Recovery													
Standard	IEC/EN/UL 60950-1 2nd Edition, IEC/EN/UL 60065 UL 1310													
Safety	CB/ cULus/FCC/GS/CE/PSE													